

Lecture 06.01 Analog-to-digital and digital-to-analog conversion

Most sensors and actuators, which are necessary components for control systems, have as input and output *analog signals*. These are continuous in time and can take on a virtually infinite number of real values. In preceding chapters, we have learned that computers work with *binary digital signals*, which communicate information by changing voltage between conventional levels representing logical true and false. How can a binary digital signal represent an analog signal and *vice versa*?

analog signals

binary digital signals

06.01.1 Analog-to-digital conversion and analog outputs

Analog-to-digital conversion (ADC) is the process by which a binary digital signal is made to represent an analog signal. This proceeds in three operations, as illustrated in **Figure 06.2**:

ADC

sampling the analog signal is *sampled*: measured at discrete moments in time, usually at a fixed *sample period* T (i.e. *sample rate* $1/T$ or *angular sample rate* $2\pi/T$);

sampling

sample period

sample rate

angular sample rate

rate

quantization

quantization the sampled measurement is *quantized*: represented by one of a finite set of values limited by the number of bits available in binary conversion; and

binary conversion the quantized measurement is converted to binary: given a binary representation such that it can be represented by a binary digital signal.




Figure 06.2: the operations required to convert an analog to a binary digital signal.

It is convenient to give a name to the measurement after it is sampled, but before it is quantized: a *discrete signal*,¹ which is represented mathematically as a sequence of real numbers paired with corresponding time

discrete signal

¹Sometimes this is called a *digital* signal, but we reserve that term for (usually binary-) quantized signals.

intervals (usually fixed). These sequences are either denoted as functions of an integer n or its product nT with a fixed sample period T .²

analog inputs A microcontroller, such as the myRIO, frequently has at least a few *analog inputs* (AIs): voltage measurement channels with ADC. The ADC takes time, so a lag is introduced in the process. Microcontrollers with an FPGA (like the myRIO) can frequently use it perform much faster ADC than those without.

For details about programming the myRIO analog inputs, see [Resource 14](#).

06.01.2 Digital-to-analog conversion and analog outputs

analog outputs Microcontrollers also commonly have at least a few *analog outputs* (AOs): channels that can programmatically produce an analog signal voltage in some range (usually something like $[0, 5]$ V or $[-10, +10]$ V). But, as we know, that continuous output once had a digital representation, so it can only construct a continuous representation of some finite number of voltage levels.

DAC The process of converting a digital signal to an analog signal is called *digital-to-analog* conversion (DAC). It is essentially the opposite process as ADC; the key move is to convert a discrete signal to a continuous signal. Considered broadly, it is the approximation of a discrete *function* by a continuous one, which is called “curve fitting”: an attempt to fill-in continuous values in the intermediate time between discrete samples.

zero-order hold There is a tradeoff here between accuracy and speed because curve fitting requires computation time. In embedded computing applications, it is frequently more-important to immediately represent the realtime output than to be accurate with intermediate approximations, especially if (as is usually the case) output resolution is sufficient. This suggests the ubiquitous method of the *zero-order hold*, which simply maintains the previous sample value throughout the intermediate sample period, yielding a step-like analog signal. While this introduces some high-frequency noise, it is usually the best option.

For details about programming the myRIO analog outputs, see [Resource 14](#).

²These are distinct mathematical functions. Sometimes we call a function of integer n a sequence and a function of nT a discrete function. Even this obscures some details, but a precise mathematical treatment is unnecessary for our purposes.